Winstar Display Co., LTD
華凌光電股份有限公司
WEB: http://www.winstar.com.tw E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF35-320240LD#0S1-FC

General Specifications

Item	Dimension	Unit
Size	3.5	inch
Dot Matrix	320 x RGB x 240(TFT)	dots
Module dimension	76.84 x 63.84 x 4.37	mm
Active area	70.08 x 52.56	mm
Dot pitch	0.073 x 0.219	mm
LCD type	TFT, Normally White, Transmissive	
View Direction	12o'clock	
Gray Scale Inversion Direction	6 o'clock	
Aspect Ratio	4:3	
Backlight Type	LED ,Normally White	
With /Without TP	With RTP	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

WINSTAR DISPLAY CO., LTD

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	℃
Storage Temperature	TST	-30	—	+80	℃

Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For LCM	VCC	—	3.0	3.3	3.6	V
Supply Current For LCM	ICC	—	—	8.6	15	mA

Interface


Pin	Symbol	Function
1	**LED-**	Power for LED backlight cathode
2	**LED-**	Power for LED backlight cathode
3	**LED+**	Power for LED backlight anode
4	**LED+**	Power for LED backlight anode
5	**YU**	Top electrode
6	**XL**	Left electrode
7	**NC**	No connect
8	**/RESET**	Hardware reset
9	**SPENA**	Chip select pin of serial interface
10	**SPCLK**	Clock pin of serial interface
11	**SPDAT**	Data input pin in serial mode
12	**B0**	Data bus
13	**B1**	Data bus
14	**B2**	Data bus
15	**B3**	Data bus
16	**B4**	Data bus
17	**B5**	Data bus
18	**B6**	Data bus
19	**B7**	Data bus
20	**G0**	Data bus
21	**G1**	Data bus
22	**G2**	Data bus
23	**G3**	Data bus
24	**G4**	Data bus
25	**G5**	Data bus
26	**G6**	Data bus


WINSTAR DISPLAY CO.,LTD

27	**G7**	Data bus
28	**R0**	Data bus
29	**R1**	Data bus
30	**R2**	Data bus
31	**R3**	Data bus
32	**R4**	Data bus
33	**R5**	Data bus
34	**R6**	Data bus
35	**R7**	Data bus
36	**HSYNC**	Line synchronization signal
37	**VSYNC**	Frame synchronization signal
38	**DCLK**	Dot-clock signal and oscillator source
39	**NC**	No connect
40	**NC**	No connect
41	**VCC**	Power Supply
42	**VCC**	Power Supply
43	**YD**	Bottom electrode
44	**XR**	Right electrode
45	**NC**	No connect
46	**NC**	No connect
47	**NC**	No connect
48	**SEL2**	Input pin to select input interface mode
49	**SEL1**	Input pin to select input interface mode
50	**SEL0**	Input pin to select input interface mode
51	**NC**	No connect
52	**DE**	Display enable pin from controller. Internal pull high Connect to VCCIO or floating if not used
53	**DGND**	System ground pin of the IC. Connect to system ground.
54	**AVSS**	Grounding for analog circuit Connect to system ground


WINSTAR DISPLAY CO., LTD

Contour Drawing






PinNo.	Symbol	PinNo.	Symbol
1	LED-	28	R0
2	LED-	29	R1
3	LED+	30	R2
4	LED+	31	R3
5	YU	32	R4
6	XL	33	R5
7	NC	34	R6
8	/RESET	35	R7
9	SPENA	36	HSYNC
10	SPCLK	37	VSYNC
11	SPDAT	38	DCLK
12	B0	39	NC
13	B1	40	NC
14	B2	41	VCC
15	B3	42	VCC
16	B4	43	YD
17	B5	44	XR
18	B6	45	NC
19	B7	46	NC
20	G0	47	NC
21	G1	48	SEL2
22	G2	49	SEL1
23	G3	50	SEL0
24	G4	51	NC
25	G5	52	DE
26	G6	53	DGND
27	G7	54	AVSS



SCALE 100/1



Detail A
SCALE 2/1

The non-specified tolerance of dimension is ±0.3 mm .

WINSTAR DISPLAY CO.,LTD