SPECIFICATIONS

CUSTOMER	:	
SAMPLE CODE	:	SH800480T030-ZHR06
MASS PRODUCTION CODE	:	PH800480T030-ZHR06
SAMPLE VERSION	:	01
SPECIFICATIONS EDITION	:	001
DRAWING NO. (Ver.)	:	JLMD-PH800480T030-ZHR06_001
PACKAGING NO. (Ver.)	:	

Customer Approved

Date:

POWERTIP
2024.01.25
JS RD APPROVED

Approved	Checked	Designer
劉進 Jin Liu	陳璐 Lu Chen	王琦 Qi Wang

■ Preliminary specification for design input

□ Specification for sample approval

POWERTIP TECH. CORP.

Represented by:

FIRST Components s.r.l.
www.first-components.com
technical@first-components.com
+39 0332 1888005

SPECIFICATIONS

Features

Item	Standard Value
Display Resolution	800 * 3 (RGB) * 480 Dots
LCD Type	Full Viewing Angle, Normally Black , Transmissive type
Screen size(inch)	5.0 inch
Surface treatment	Anti-Glare
Color configuration	RGB Vertical Strip
Interface	Parallel RGB (Data), SPI (Configuration)
Optical Type	OCR
ROHS	THIS PRODUCT CONFORMS THE ROHS OF PTC

Note: For detailed information please refer to IC data sheet:

Primacy(TFT LCD): Sitronix: ST7262

Mechanical Specifications

Item	Standard Value	Unit
Outline Dimension	145.56(W) x 102.36(L) x 7.3(H)	mm

LCD panel

Item	Standard Value	Unit
Active Area	108.0 (W) x 64.8(L)	mm

Note: For detailed information please refer to LCM drawing

first components

Absolute Maximum Ratings

Item	Symbol	Condition	Min.	Max.	Unit
Power Supply for TFT Panel	VDD	GND=0	-0.3	4.5	V
Power Supply for Backlight Unit	VCC	GND=0	-0.3	+20.0	V
Operating Temperature	T_{OP} (Ts)	Note 1	-20	70	°C
Storage Temperature	T_{ST} (Ta)	Note 2	-30	80	°C
Storage Humidity	H_D	Ta ≦ 60 °C	10	90	%

The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

Note 1：Ts is the temperature of panel's surface.
Note 2：Ta is the ambient temperature of samples.

DC Electrical Characteristics

GND = 0V, Ta = 25°C

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Power Supply for TFT Panel	VDD	GND=0V	3.0	3.3	3.6	V
Power Supply for Backlight Unit	VCC	GND=0V	5	12	15	V
Input Voltage for TFT Panel	V_{IH}	GND=0V	0.7VDD	-	VDD	V
	V_{IL}	GND=0V	0	-	0.3VDD	
Supply Current for TFT Panel	IDD	IDD@VDD=3.3V	-	(75)	(110)	mA
Supply Current for Backlight Unit	ICC	ICC@VCC=5V	-	(250)	(380)	
Supply Current for Backlight Unit	ICC	ICC@VCC=12V	-	(110)	(160)	
Input Voltage for PWM Signal	VPH	GND=0V	1.2	-	-	V
	VPL	GND=0V	-	-	0.4	V
Dimming Clock Rate	fP	GND=0V	5	-	100	KHz

first components

Optical Characteristics

VDD= 3.3 V, Ta=25°C

Item	Symbol		Condition	Min.	Typ.	Max.	unit	-
Response time	Tr+Tf		Ta = 25°C θX, θY = 0°	-	37	56	ms	Note 2
Viewing angle	Top	θY+	CR ≥ 10		80	-	Deg.	Note 4
	Bottom	θY-			80	-		
	Left	θX-			80	-		
	Right	θX+			80	-		
Contrast ratio	CR		Ta = 25°C θX , θY = 0°	650	800	-	-	Note 3
Color of CIE Coordinate	White	X		(0.27)	(0.32)	(0.37)	-	Note1
		Y		(0.30)	(0.35)	(0.40)		
	Red	X		(0.56)	(0.61)	(0.66)		
		Y		(0.30)	(0.35)	(0.40)		
	Green	X		(0.31)	(0.36)	(0.41)		
		Y		(0.53)	(0.58)	(0.63)		
	Blue	X		(0.08)	(0.13)	(0.18)		
		Y		(0.06)	(0.11)	(0.16)		
Average Brightness (With LCD & TP)*1	IV		VCC=12.0V PWM="High" (Duty=100%)	(680)	(850)	-	cd/m2	Note1
Uniformity (With LCD & TP)*2	△B		VCC=12.0V PWM="High" (Duty=100%)	70	-	-	%	Note1

Backlight Unit Characteristics

Maximum Ratings


Item	Symbol	Min.	Max.	Unit	Remark
LED Forward Current	I_F	-	25*3	mA	-
LED Reverse Voltage	V_R	-	1.2*6	V	
Power Dissipation	PD		1500	mW	

Electrical / Optical Characteristics

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
LED Voltage	V_L	18.0	19.0	-	V	Note1
LED Current	I_L	-	60	-	mA	-
LED life time	-	50,000	-	-	H_r	Note2

Note 1: The LED Supply Voltage is defined by the number of LED at Ta=25℃ and I_L =60 mA.
Note 2: The “LED life time” is defined as the module brightness decrease to 50% original brightness at Ta=25℃ and I_L =60 mA. The LED life time could be decreased if operating I_L is larger than 60 mA.

Internal Circuit



Interface Pin Description

TFT LCM Interface

Pin#	Name	Description
1	GND	Power ground.
2	VDD	Power for Digital Circuit.
3	VDD	Power for Digital Circuit.
4	VCC	Power For LED backlight.
5	VCC	Power For LED backlight.
6	PWM	Shutdown & Dimming control input for backlight. Do not allow this pin to float. “Hi” =100%, “Low” = 0%.
7	GND	Power ground.
8	R0	Red Data.
9	R1	Red Data.
10	R2	Red Data.
11	R3	Red Data.
12	GND	Power ground.
13	R4	Red Data.
14	R5	Red Data.
15	R6	Red Data.
16	R7	Red Data.
17	GND	Power ground.
18	G0	Green Data.
19	G1	Green Data.
20	G2	Green Data.
21	G3	Green Data.
22	GND	Power ground.
23	G4	Green Data.
24	G5	Green Data.
25	G6	Green Data.
26	G7	Green Data.
27	GND	Power ground.
28	B0	Blue Data.
29	B1	Blue Data.

first components

Pin#	Name	Description
30	B2	Blue Data.
31	B3	Blue Data.
32	GND	Power ground.
33	B4	Blue Data.
34	B5	Blue Data.
35	B6	Blue Data.
36	B7	Blue Data.
37	GND	Power ground.
38	HS	Line synchronization signal. Horizontal Sync Input.
39	VS	Frame synchronization signal. Vertical Sync Input.
40	GND	Power ground.
41	DE	Data Enable.
42	GND	Power ground.
43	DCLK	Sample clock. Data will be latched at the falling edge of DCLK.
44	GND	Power ground.
45	CS/ ID1	Serial communication chip selection/ID[4:1]These pins select LCM type. See NOTE1
46	SDIN/ ID2	Serial communication data/ ID[4:1]These pins select LCM type. See NOTE1
47	SCK/ ID3	Serial communication clock/ ID[4:1]These pins select LCM type. See NOTE1
48	DISPLAY CONTROL / ID4	Display Enable(Hi Active)./ ID[4:1]These pins select LCM type. See NOTE1
49	/RESET	Global Reset (Low Active).
50	GND	Power ground.

Note1:

ID Pins Definition:


	PIN 45 ID1	PIN 46 ID2	PIN 47 ID3	PIN 48 ID3
3.5” Module	X	0	0	X
4.3” Module	X	1	0	X
5.0” Module	X	0	1	X
7.0” Module	X	1	1	X

1. Resistor = 10k ohm
2. “X” = No use

Capacitive Touch Panel (CTP) Interface

Pin No.	Symbol	Function
1	GND	Touch Panel Ground.
2	TPVDD	Power Supply Voltage (3.3V)
3	SCL	I2C Clock
4	SDA	I2C Data
5	INT	The interrupt the CTP to the Host
6	RST	RESET

first FC components



NOTES:
1.LCD TYPE:TFT LCD
2.LCD DISPLAY:Normally Black/TRANSMISSIVE
3.The tolerance unless classified ±0.3mm
4.a :P0.5*49=24.5±0.05 ; W=0.35±0.05
b :P0.5*5=2.5±0.05 ; W=0.35±0.05
5. :Kapton tape; :Component area; :Stiffener(SUS t=0.2mm to GND)
:Aluminum Foil Conductive Adhesive Tape; :EMI Film;
6.LCM FPC suggested connector : "Hirose" FH12A-50S-0.5SH or compatible.
6.T/P FPC suggested connector : "Hirose" FH34SRJ-6S-0.5SH(50) or compatible.

REV		REV BY	DATE
007			
006			
005			
004			
003			
002			
001	NEW DRAWING	Maeve	2024/01/24

PART NO:
DRAWING NAME :
TITLE: LCD MODULE DRAWING
PH800480T030-ZHR06

久正光電股份有限公司
POWERTIP TECHNOLOGY CORPORATION

Design		(3)	Surface		
Check		Unit	MM	Material	
Approve		Scale	FIT	Thickness	
		Page	1/1	Quantity	

Length(Min) (mm) \ Tolerance \ Precision	Level Precision
1 ~ 4	-
4 ~ 16	-
16 ~ 63	-
63 ~ 250	-
250 ~ 1000	-

first components
sales@first-components.com