SPECIFICATION

MODULE NO.: WF84-1024768AL#0PW4-FC

General Specifications

Item	Dimension	Unit
Screen Diagonal	8.4	inch
Number of Pixels	1024 × 3(BGR) × 768	dots
Module dimension	199.5 × 149.0 × 11.5	mm
Active area	170.8032 (H) × 128.1024(V)	mm
Pixel pitch	0.1668 × 0.1668	mm
Display Mode	Normally Black , Transmissive	
Viewing Angle	80/80/80/80	
TFT Drive IC	ST5821AH+ST5084AA or Equivalent	
TFT Interface	LVDS	
Backlight Type	LED, Normally White	
Aspect Ratio	4:3	
Side screw torque	Typ:0.9 Max:1.3 (Unit,Kgf-cm)	
Touch Panel	Without Touch Panel	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

Represented by:
FIRST Components s.r.l.
www.first-components.com
sales@first-components.com
+39 0332 1888005

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-30	–	+80	℃
Storage Temperature	TST	-30	–	+80	℃

Electrical Characteristics

Operating conditions:

Item		Symbol	Min	Typ	Max	Unit
Supply Voltage For Logic		V_{DD}	3.0	3.3	3.6	V
Power Supply For Current		V_{DD}=3.3V	–	330	495	mA
Input Voltage	H level	V_{IH}	0.7V_{DD}	–	V_{DD}	V
	L Level	V_{IL}	GND	–	0.3V_{DD}	V

WINSTAR DISPLAY CO., LTD
components

Interface

LCM PIN Definition


Pin No.	Symbol	Function	Remark
1	VDD	Power supply	
2	VDD	Power supply	
3	GND	Ground	
4	GND	Ground	
5	Link0-	0- LVDS differential data input **(D0N)**	
6	Link0+	0+ LVDS differential data input **(D0P)**	
7	GND	Ground	
8	Link1-	1- LVDS differential data input **(D1N)**	
9	Link1+	1+ LVDS differential data input **(D1P)**	
10	GND	Ground	
11	Link2-	2- LVDS differential data input **(D2N)**	
12	Link2+	2+ LVDS differential data input **(D2P)**	
13	GND	Ground	
14	CLKIN-	- LVDS differential clock input **(CLKN)**	
15	CLKIN+	+ LVDS differential clock input **(CLKP)**	
16	GND	Ground	
17	Link3-	3- LVDS differential data input **(D3N)**	
18	Link3+	3+ LVDS differential data input **(D3P)**	
19	MODE	Bit 6/8:Low(6 Bit);High(8 Bit)	
20	SC	Scan direction selector (Low: Normal ;High: Reverse)	

CN2

Pin No.	Symbol	Function	Remark
1	NC	No connection	
2	NC	No connection	
3	LED C1	LED_ Cathode 1	
4	LED A1	LED_ Anode 1	
5	LED A2	LED_ Anode 2	
6	LED C2	LED_ Cathode 2	


WINSTAR DISPLAY CO., LTD
FIRST Components

Contour Drawing



The non-specified tolerance of dimension is ±0.5 mm .

WINSTAR DISPLAY CO.; LTD
first components



CN2

Pin	Symbol
1	NC
2	NC
3	LED C1
4	LED A1
5	LED A2
6	LED C2

CN1

Pin	Symbol
1	VDD
2	VDD
3	GND
4	GND
5	Link0-
6	Link0+
7	GND
8	Link1-
9	Link1+
10	GND
11	Link2-
12	Link2+
13	GND
14	CLKIN-
15	CLKIN+
16	GND
17	Link3-
18	Link3+
19	MODE
20	SC

The non-specified tolerance of dimension is ±0.5 mm .

WINSTAR DISPLAY CO.,LTD
first components