WINSTAR Display

OLED SPECIFICATION

Model No:

TSL025664BF111XXXX00

first FC components

Represented by:

FIRST Components s.r.l.
www.first-components.com
sales@first-components.com
+39 0332 1888005

SPECIFICATION Version: 0

CUSTOMER :	
MODULE NO. :	**TSL025664BF111XXXX00**

APPROVED BY: **(FOR CUSTOMER USE ONLY)**	

SALES BY	APPROVED BY	CHECKED BY	PREPARED BY
first FC components			
RELEASE DATE:			

■APPROVAL FOR SPECIFICATIONS ONLY

□APPROVAL FOR SPECIFICATIONS AND SAMPLE

MODEL NO：

RECORDS OF REVISION			DOC. FIRST ISSUE
VERSION	DATE	REVISED PAGE NO.	SUMMARY
0	2022/10/05		First release

first FC components

Contents

1.General Specification

2.Electrical Characteristics

3.Contour Drawing

4.Interface Pin Function

5.Other

6.Inspection specification

first FC components

1.General Specification

1.1. Type: capacitive touch panel

1.2. Input mode: finger

1.3. Structure and material:

Structure	Material	Thickness	Remark
Cover lens	Glass	0.7mm	強化玻璃
Upper circuits	ITO film	0.125mm	-
Back tape	Adhesive	0.1mm	-

1.4. Dimension:

Item	Description	Unit
Outline dimension	89.2x29	mm
View Area	78.78x21.18	mm
Total thickness	1.025（with DSA）	mm
Length of FPC	33.2	mm
Thickness of FPC terminal	0.3	mm

first FC components

2.Electrical Characteristics

Item	Specification
IC model	FT6336U
Interface	I2C
Surface hardness	≥6H
Supply voltage	DC 2.8V~3.3V
Support touch mode	2 points


first FC components

3.Contour Drawing

FRONT VIEW

SIDE VIEW

BACK VIEW



PIN NO.	SYMBOL
1	GND
2	VDD
3	INT
4	SDA
5	SCL
6	RST
7	GND
8	GND
9	GND
10	GND

The non-specified tolerance of dimension is ±0.2mm.

4. Interface Pin Function

Pin No.	Symbol	Description
1	GND	Ground.
2	VDD	Power Supply Voltage of CTP
3	INT	External interrupt to the host
4	SDA	I2C data input and output
5	SCL	I2C clock input
6	RST	External Reset, Low is active
7	GND	Ground.
8	GND	Ground.
9	GND	Ground.
10	GND	Ground.

first FC components

5.Other

5.1. Environmental characteristics

Item	Specification
Operating Temp.	-20℃～70℃
Storage Temp.	-30℃～80℃

Note: Testing environment is under normal atmospheric pressure. When the ambient temperature is above 65℃,the humidity is allowed to be below 50%RH

5.2. Optical characteristics

Item	Specification	Remark
Light transmission	≧83%	-

5.3. Reliability and Durability test

Item	Condition	Criteria
High temperature storage	80℃ for 72H	After the above test, the touch panel is to be exposed at room condition for 24H or more. Must be within the spec.
Low temperature storage	-30℃ for 72H	
High temperature &high humidity storage	60℃,90%RH for 72H	
Thermal shock	-30℃（0.5H）～80℃（0.5H），10 cycles	

first FC components


6. Inspection specification

Inspection Standard:

MIL-STD-105E table normal inspection single sample level II.

Definition

1 Major defect : The defect that greatly affect the usability of product.
2 Minor defect : The other defects, such as cosmetic defects, etc.
Definition of inspection zone:





Zone A: Active Area
Zone B: Viewing Area except Zone A
Zone C: Outside Viewing Area
Note: As a general rule, visual defects in Zone C are permissible, when it is no trouble of quality and assembly to customer`s product.

Inspection Methods

1 The general inspection : Under fluorescent light illumination: 750~1500 Lux, about 30cm viewing distance, within 45º viewing angle, under 25±5°C.
2 The luminance and color coordinate inspection : By SR-3 or BM-7 or the equal equipments, in the dark room, under 25±5°C.

NO	Item	Criterion	AQL
01	Electrical Testing	No function	0.65
02	Black or white spots on OLED (display only)	2.1 White and black spots on display ≦0.25mm, no more than four white or black spots present. 2.2 Densely spaced: No more than two spots or lines within 3mm.	2.5

<table>
<tr><th>NO</th><th>Item</th><th>Criterion</th><th>AQL</th></tr>
<tr><td rowspan="2">03</td><td>OLED black spots, white spots, contamination (non-display)</td><td>3.1 Round type :
As following drawing
Φ=(x + y) / 2


<table><tr><th>SIZE</th><th>Acceptable QTY</th><th>Zone</th></tr><tr><td>Φ≦0.10</td><td>ignore</td><td>A+ B</td></tr><tr><td>0.10＜Φ≦0.20</td><td>3</td><td>A+ B</td></tr><tr><td>0.20＜Φ≦0.25</td><td>1</td><td>A+ B</td></tr><tr><td>0.25＜Φ</td><td>0</td><td>A+ B</td></tr></table></td><td>2.5</td></tr>
<tr><td>3.2 Line type : (As following drawing)


<table><tr><th>Length</th><th>Width</th><th>Acceptable Q TY</th><th>Zone</th></tr><tr><td>---</td><td>W≦0.02</td><td>ignore</td><td>A+B</td></tr><tr><td>L≦3.0</td><td>0.02＜W≦0.03</td><td rowspan="2">4</td><td>A+B</td></tr><tr><td>L≦2.5</td><td>0.03＜W≦0.05</td><td>A+B</td></tr><tr><td>---</td><td>0.05＜W</td><td>As round type</td><td></td></tr></table></td><td>2.5</td></tr>
<tr><td>04</td><td>bubbles</td><td>If bubbles are visible, judge using black spot specifications, not easy to find, must check in specify direction.
<table><tr><th>Size Φ</th><th>Acceptable Q TY</th><th>Zone</th></tr><tr><td>Φ≦0.20</td><td>ignore</td><td>A+B</td></tr><tr><td>0.20＜Φ≦0.50</td><td>2</td><td>A+B</td></tr><tr><td>0.50＜Φ≦1.00</td><td>0</td><td>A+B</td></tr><tr><td>Total Q TY</td><td>2</td><td></td></tr></table></td><td>2.5</td></tr>
<tr><td>05</td><td>Scratches</td><td>Follow NO.3 OLED black spots, white spots, contamination.</td><td></td></tr>
</table>