SMART DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.

華凌光電股份有限公司

Represented by:

FIRST Components s.r.l.
www.first-components.com
technical@first-components.com
+39 0332 1888005

SPECIFICATION

CUSTOMER : _____

MODEL NO. : WL0F0007000A8GDAASA01-FC

APPROVED BY: (FOR CUSTOMER USE ONLY)	

SALES BY	APPROVED BY	CHECKED BY	PREPARED BY
first FC components		Paul Chen	Debby Hsu

VERSION	DATE	REVISED PAGE NO.	SUMMARY
0	2023/8/23		

Summary

7 Inch Smart Display (RS485 series) Features

1. +12V power supply input with 5V to 16V dynamic range power input, the power consumption is around 8 Watt.
2. Self testing after booting function.
3. RS485 communication interface.
4. Built in flash memory, store the font and Object Dictionary Data.
5. Support capacitive touch panel (CTP).
6. Embedded buzzer controlled by Master Device.
7. HOST can be used on multiple platforms, such as Computer (with USB to RS-485 Dongle), MCU.

first FC components


Product information

General information

Item	Standard Value	Unit
Operating voltage	5~16V	Vdc
Communication Interface	RS485 differential ± 3.3	Vpp
MCU	STM32F746	N/A
Flash Memory	16	MB
SDRAM Frequency	108	MHz
LCD display size	7.0	inch
Dot Matrix	1024 x RGBx600(TFT)	dot
Module dimension	184.1(W) x 103.8(H) x 22(D)	mm
Active area	154.2144 x 85.92	mm
Dot pitch	0.1506 x 0.1432	mm
Brightness	Min: 800; Typ: 850	cd/m^2
LCD type	TFT, Normally Black, Transmissive	
View Direction	85/85/85/85	
Aspect Ratio	16:9	
With /Without TP	With CTP	
Surface	Glare	

first FC components

Contour Drawing



POWER JACK

2 — ◎ — 1

(GND) (12V)

CON3

PIN	SYMBOL
1	VDD3V
2	JTAG_SWCLK
3	GND
4	JTAG_SWDIO
5	NRST
6	GND

CON2

PIN	SYMBOL
1	+12V
2	GND
3	NC
4	NC
5	GND
6	GND
7	NC
8	NC
9	NC
10	NC
11	NC
12	GND
13	NC
14	RS485_B
15	RS485_A
16	GND

The non-specified tolerance of dimension is ±0.3mm.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	℃
Storage Temperature	TST	-30	—	+80	℃

Note: Device is subject to be damaged permanently if stresses beyond those absolute maximum ratings listed above
1. Temp. ≦60℃, 90% RH MAX. Temp.＞60℃, Absolute humidity shall be less than 90% RH at 60℃

Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage	VIN	—	5	12	16	V
Supply current	I(mA)	—	—	675	—	mA

BOM

Item	Description	Remark
LCM	WF70-1024600A8L#BSP3-FC	
PCBA	SV10007R00AAA00N0108	

Interface

CON2 definition:

Pin	Symbol	Function	Remark
1	+12V	Power supply V+	Input
2	GND	Power supply GND input	Input
3	NC	_	_
4	NC	_	_
5	GND	Power supply GND input	Input
6	GND	Power supply GND input	Input
7	NC	_	_
8	NC	_	_
9	NC	_	_
10	NC	_	_
11	NC	_	_
12	GND	GND	GND
13	NC	_	_
14	RS485_B	RS485 DATA-	I/O
15	RS485_A	RS485 DATA+	I/O
16	GND	GND	GND

first FC components

CON3 definition:

Pin	Symbol	Function	Remark
1	VDD3V	3.3V power for JTAG interface	Output
2	JTAG_SWCLK	CLK pin for JTAG interface	Input
3	GND	GND for JTAG interface	Output
4	JTAG_SWDIO	Data pin for JTAG interface	I/O
5	NRST	Reset pin for JTAG interface	Input
6	GND	GND	Output
7~16	NC	_	_

first FC components